

# HEAVY DUTY SUBSTATION

ATEX IIC T6



when communication is critical

## FEATURES

- Heavy duty industrial ATEX substation
- Designed for the STENTOFON AlphaCom exchange
- Can make calls and call request to pre-programmed stations
- Robust buttons for:
  - - Call request
  - - Press to talk for optional simplex conversation
  - - Cancel
- Rugged weatherproof cabinet of lacquered steel
- Handset for soft speaking conversation
- Requires an external loudspeaker
- Relay output for control of optional signal unit
- Advanced supervision functions

## DESCRIPTION

The station is designed to satisfy ATEX regulations and carries the following approval EX de [ia] IIC T6.

Power is needed for the internal 10 W amplifier to drive an 8 Ohm or 20 Ohm speaker. The station is connected to the exchange using a 3-pair cable.

The handset microphone is always connected, thereby permitting direct answer back when receiving a call. When using the handset during conversation, the external loudspeaker is turned off.

An optionally connected call warning device will also turn off when lifting the handset for conversation. The conversation will be cancelled by placing the handset back on hook, or by pressing the "Cancel" button. The call request button can be programmed to call any number in the exchange.

The station is made for duplex conversations but can be put in simplex mode by pressing the M button in the station, or the talk button in the handset.

To provide maximum availability the station comes with advanced supervision functions. The station line test will detect if there are any faults in the network or station electronics. In addition the station supports tone test, testing the complete transmission path including microphone and speaker. The status of the stations is reported to AlphaWeb as well as to 3rd party management systems using SNMP, Syslog, OPC or the STENTOFON Software Development Kit (SDK).



Zenitel Norway AS  
Sandakerveien 24C, P.O. BOX 4498 Nydalen  
NO-0403 Oslo, Norway

Zenitel USA Inc.  
6119 Connecticut Avenue  
Kansas City, MO 64120  
800/654-3140

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1007095300	Heavy Duty Substation ATEX IIC T6	50.7 lbs.

## HEAVY DUTY SUBSTATION ATEX IIC T6

### SPECIFICATIONS

Dimensions (WXHXD)	8.5 x 27.0 x 7.4 inch.
Protection	EX de [ia] IIC T6
IP protection	Cabinet IP-65
Handset	Intrinsically safe, via zener barriers inside the EXd enclosure
Weight	50.7 lbs.
Temperature	-4°F to +131°F
Internal power amplifier	10 W
Power amp operating voltage	24-30 VDC
Loudspeaker	External 8 or 20 ohms loudspeaker must be installed
Material	Cabinet is in laquered steel, light beige
Keypad	3 x large buttons, M, DAK, C
Cable requirement	2 pairs for audio, 1 pair for 24-30 VDC to power amplifier
Max loudspeaker output	5 W with 20 ohms loudspeaker 10 W with 8 ohms loudspeaker
Distance to exchange for audio	13,123 ft. (18 AWG - 0.035 inch.) 11,155 ft. (20 AWG - 0.031 inch.) 6,561 ft. (22 AWG - 0.02 inch.)
Distance to power supply	8 ohms loudspeaker, 24 VDC 0.02 inch.: 230 ft. 0.03 inch.: 328 ft. 0.04 inch.: 657 ft.  8ohms loudspeaker, 30 VDC 0.02 inch.: 492 ft. 0.03 inch.: 820 ft. 0.04 inch.: 1,477 ft.  20ohms loudspeaker, 24 VDC 0.02 inch.: 492 ft. 0.03 inch.: 820 ft. 0.04 inch.: 1,312 ft.  20ohms loudspeaker, 30 VDC 0.02 inch.: 1,148 ft. 0.03 inch.: 2,132 ft. 0.04 inch.: 3,280 ft.
Control of external call device	Potential free relay contact (3A, 30 VDC)
Connector type	Screw terminals
Compliance	CE, FCC Part 15

