

CEILING SUBSTATION

GS-400 SYSTEM



when communication is critical

FEATURES

- Enhanced Sound Monitoring
- Wide Frequency Response
- Heavy Duty Construction
- Unobtrusive Appearance
- Easy to Install
- Clear Two-Way Communication

DESCRIPTION

The 426 is a high quality ceiling mounted intercom and audio monitoring substation using a 4" speaker and condenser microphone. It is a metal full range speaker complete with speaker, microphone, baffle and necessary electronics. The 426 is ideal for audio monitoring in security applications and in hospital CAT scan or Cath Lab rooms. It appears as a standard paging speaker, and provides clear two-way intercom from a 410 master station. The 426 will operate on the GS-400 one-to-one intercom system.



SPECIFICATIONS

Baffle:	Round, 22 ga. steel, hidden mounting studs
Finish:	Zinc coated, finished in white baked epoxy
Size:	7 7/8" round, 3 1/2" deep
Speaker:	4", capable of 3 watt output, 45 ohm
Frequency:	180 Hz - 9 Khz. Sensitivity 93 db
Magnet:	1 oz., barium ferrite ceramic
Microphone:	Electret condensor type with 100/300 mv output
Connectors:	Screw Terminals
Cabling:	(3) pair twisted #22 AWG from GS-410 Master
Mounting:	Use #1830 backbox and #1831 ceiling bridge

www.stentofonusa.com

Zenitel USA, Inc.
6119 Connecticut Avenue
Kansas City, MO 64120
800/654-3140

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1000142600	Ceiling Speaker	

CEILING SUBSTATION

ORDER NUMBER

1000142600

STENTOFON products are developed and marketed by Zenitel USA. ZENITEL USA reserves the right to modify designs and alter specifications without prior notice, in pursuance of a policy of continuous improvement.
© 2009 Zenitel USA.

sales@stentofonusa.com