

CU-10

CENTRAL UNIT 10 EXTENSIONS



when communication is **critical**

FEATURES

- Central unit 10 lines for the CTB system
- Operates with CTB-10 and CTB-10 W/V01 panel units
- AUX / Alarm input
- Output to Public Address system
- 24 VDC power supply



SPECIFICATIONS

| | |
|-----------------------------|---|
| Material / finish: | Aluminium / black |
| Mounting | Bulkhead with 4 x 4 mm screws |
| Terminals | Plugable screw terminals for cable max. 2,5 mm ² |
| Fuses | F1, F2, F3, F4, 1 A 5 x 20 |
| DIP-switches | For PA-zones, set priority, set receive call |
| Pot.meter | For volume setting line 1-5, 6-10 |
| Dimension (mm) | 400W x 400H x 120D |
| Weight | Approx. 2.6 kg |
| External connections | 4x Operation panels, up to 10 substations, AUX, PA |
| AUX input | 0 dB 0,775 V/600 ohm |
| Alarm contact | Potential free N/O |
| Frequency range | 200 Hz - 8 KHz (-3 dB) |
| Temperature operating | -20 + 55°C |
| Power supply | 20 - 32 VDC |
| Power consumption at 24 VDC | 2.5 A |
| Output power | 30 W per 10 lines |
| Output impedance | 20 ohm per line |

| ORDER NUMBER | DESCRIPTION | SHIP WEIGHT |
|--------------|----------------------------|-------------|
| CU-10 | Central Unit 10 extensions | 2.6 kg |

CU-10 CENTRAL UNIT 10 EXTENSIONS

