

HB-105

TELEPHONE TONE CALLER



when communication is **critical**

FEATURES

- Telephone line powered (no mains voltage or batteries required)
- Greatly reduced installation costs
- 105 dBA output
- Volume control
- REN of 1.5
- Maintenance-free operation
- For weather exposed and noisy areas

DESCRIPTION

HB-105 loud tonecaller is powered by the PABX and PSTN line voltage (60-100 V AC). A variable output (85-105 dBA) is possible by means of a potentiometer located within the unit. HB-105 is a suitable additional ringer device for telephones in weather-exposed and noisy areas.



SPECIFICATIONS

Colour	Yellow case & black base
Dimensions (Ø x H)	90 x 118
Mounting	4 x 4 mm screws
Weight	0.4 kg
Cable entry	1 x PG-9
Connections	Screw terminals
Input voltage	60 - 100 Vac line powered
Output SPL	85 - 105 dB / 1 m
Frequency	120 Hz
Volume control	By potentiometer
Temperature range	-20 to + 70°C
Protection	IP-66

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
HB-105	Telephone Tone caller 60 - 100 VAC, 105 dB, WP	0.4 kg

HB-105 TELEPHONE TONE CALLER

