

SON-16

COMBINED AUDIO VISUAL SIGNAL UNIT



when communication is **critical**

FEATURES

- **High sound output**
- **High flash energy**
- **Low current consumption**
- **10 Alarm tones including bell sound**
- **Automatic synchronisation**
- **2 stage of alarm**
- **Complies with European norms for fire alarm installations**
- **Small and compact housing**

DESCRIPTION

The Combined Sounder & Flash alarm type SON 16 is a combined audible and visual warning device which is well suited for fire and security purposes incorporating high sound output, low current consumption, high quality and simple installation.

It offers many features that makes the sounder unique including 10 field programmable tones one of which is a first in sounder technology - an electronic simulated bell, reverse polarity protection and automatic synchronisation.



SPECIFICATIONS

Operation voltage	24V DC
Current	248 mA
Sound pressure output	95 dB(A), 1M
Flash energy	5 Joules (Ws)
Flash frequency	60 flashes/min.
Volume control	-25 dB
Rating	100%
Operating temperature	-25°C to +55°C
Humidity	0-90% at 50C°
IP-class	IP-55
Housing	Taxalan FR.ABS
Cable entry	Ø20 (knockout)
Lens	Polycarbonate
Dimensions (mm)	98W x 176H x 83D
Weight	0,51 kg

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
SON-16	Combined audio visual alarm, 24V DC waterproof	0,51 kg

SON-16 COMBINED AUDIO VISUAL SIGNAL UNIT

