

VMP-503

MAIN STATION WITH LOUDSPEAKER



when communication is **critical**

FEATURES

- Designed for use with ACM exchanges and for wall mounting.
- Handsfree open conversation or private when used with Handset VMP-211 or VMP-250.
- Built-in loudspeaker
- Built-in electret microphone gives clear sound
- Keyboard with large digits
- C-key for cancelling calls
- M-key for manual switching of speech direction (simplex).
- Voice operating duplex speech.
- Full duplex when connected with handset VMP-221
- Public Address messages via General Call and Group
- Calls with automatic answer back, are available
- Audio Programmes can individually be selected and received.
- Screw terminals for easy connection of Installation cables and optional

SPECIFICATIONS

Operation voltage	Powered from exchange
Cable requirements	Twisted 2 pairs 0.5mm ² outer screen
Connections	Screw terminals
Loudspeaker Output	1.4 W
Internal Loudspeaker impedance	63 ohm
Frequency range	300 - 5000 Hz
Temperature range	5 - 55 °C
Mic. Impedance for external handset	200 - 600 ohm
Material	Bayblend plastic Membrane keyboard foil of cured PVC
Colour	Grey
IP- class	IP-65
Dimensions (mm)	124W x 224H x 63D
Weight	0,75 kg



ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
VMP-503	Main station with built in 50 ohm loudspeaker waterproof	0.65 kg
Supplementary equipment		
VMP-211	Wall mounted handset	0.9 kg
VMP-250	Wall mounted handset waterproof	0.9 kg

VMP-503 MAIN STATION WITH LOUDSPEAKER

