

2220012312 CISCO2901-V/K9

Cisco 2901 Voice Bundle (PVDM3-16, FL-CUBEE10, UC license PAK)



Description

Cisco 2900 Series Integrated Services Routers offer embedded hardware encryption acceleration, voice- and video-capable digital signal processor (DSP) slots, optional firewall, intrusion prevention, call processing, voicemail, and application services. In addition, the platforms support the industries widest range of wired and wireless connectivity options such as T1/E1, T3/E3, xDSL, copper and fiber GE.

Cisco IOS® Software Universal image is installed on each ISR G2. The Universal image contains all of the Cisco IOS technology sets which can be activated with a software license. This allows your business to quickly deploy advanced features without downloading a new IOS image. Additionally, larger default memory is included to support the new capabilities.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

ENVIRONMENT

Operating temperature	32 to 104°F (0 to 40°C)
Operating relative humidity	10% to 85% noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	47 to 63 Hz
Maximum heat dissipation	511.82 BTU/hr
AC voltage	100 / 240 VAC
Current	1.5 / 0.6 A
Maximum power rating	150 W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	438.2 x 439.4 x 44.5 mm
Weight	6.1 kg
Mounting	Rack Mountable, 1HU

Accessoires



VWIC3-1MFT-T1/E1

Cisco 1-Port T1/E1 Multiflex Trunk Voice/WAN Interface Crd



Cisco Two-port Voice Interface Card - BRI (NT and TE)

VIC2-4FXO

Cisco Four-Port Voice Interface Card - FXO (VIC2-4FXO)



VIC3-4FXS/DID

Cisco Four Port Voice Interface Card - FXS and DID

page 2/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.





EHWIC-4G-LTE-G

Cisco 4G LTE EHWIC for Global

800/900/1800/2100/2600 MHz



PVDM3-16U32

Cisco PVDM3-16U32 16 to 32channel factory upgrade



EHWIC-3G-HSPA+7

Cisco 3G HSPA+7 with GPS based MC8705



SL-29-UC-K9

Cisco Unified Communications License for Cisco 2901-2951



SL-29-SEC-K9

Cisco Security License for Cisco 2901-2951



FL-CUBEE-5

Cisco Unified Border Element Enterprise License - 5 sessions



FL-CME-SRST-5

CISCO Communication Manager Express or SRST-5 seat license

SL-29-DATA-K9

Cisco Data License for Cisco 2901-2951



FL-CME-SRST-25

CISCO Communication Manager Express or SRST-25 seat license

page 3/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.