



2340110022 ETC-577B

Microphone dynamique à main haut de gamme

## Description

Microphone à main dynamique « Close-Talk » adapté à la communication vocale.

- Réponse de fréquence adaptée à la communication vocale
- Microphone directionnel Close-Talk
- Réduction du bruit de fond grâce au Close-Talk
- Ø Microphone dynamique, 175 Ω
- Cordon flexible avec switch PTT
- Étrier de suspention

# **Technical Dimensions**

page 1/3

#### www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

false

page 2/3

### www.zenitel.com info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Spécifications

### GÉNÉRAL

Type de microphone	Dynamique
Dimensions (LxHxP)	67 x 94 x 97 mm
Poids	0,33 kg
Impédance	175 Ω
Réponse en fréquence	100 - 5000 Hz
Sensibilité	0 dB = 1 V pour 1 Pa/94 dB SPL
Courbe de directivité	Cardioïde
Switch	PTT
Câble	Cordon en spirale 3 fils avec blindage
Prise	DIN à 5 pôles
Accessoires	Étrier de suspension
Indice de Protection IP	IP-22

### www.zenitel.com

### info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.