

2211100520

C3115i DECT handset with positioning

including belt clip

DISCONTINUED PRODUCT.



Description

- ✓ Positioning option allows monitoring and tracking of the DECT handset position in case of incidents.
- ✓ Water and dust resistant according to IP-65.
- ✓ Large 1.8" display, 7 lines with color-coding Dynamic display with up to 16 characters in each line, each message can contain 198 characters.
- ✓ Built-in vibrator for noisy environments or discretion is required.
- ✓ High battery capacity – LI-Ion battery.
- ✓ 2.5 mm jack for headset.
- ✓ Loud speaking and hands free function.
- ✓ Battery and belt clip included.
- ✓ A large dedicated alarm button on the top of the handset makes it easy to call for help.
- ✓ Extra function key on the right side. This is used for alarm acknowledge, send soft alarms or to call colleagues.
- ✓ Supports advanced alarm handling which contains symbols, color-code, priority, alarm ID, dynamic alarm list, extended alarm list and automatic alarms.
- ✓ Equipped with man down and motion alarm, for monitoring of movement or non movement.
- ✓ Pull cord alarm is ideal for protection against theft, personal attack or for use in distress situations

Spécifications

GENERAL

| | |
|-------------------------|---|
| Size (WxHxD) | 152 x 53 x 27 mm |
| Weight | 0.138 kg |
| Display | 1,8" 65 000 colors |
| Operational temperature | 0-40°C |
| Speech/ standby time | 16/150h |
| Ingress protection | IP65 |
| Headset interface | 2,5mm jack plug |
| Built-in vibrator | Yes |
| Menu languages | Swedish, English, Danish, German, French, Dutch, Finnish, Norwegian, Spanish, Czech, Polish, Portuguese and Italian |

DESCRIPTION

| | |
|------------|--|
| 2211100560 | Charger and Power Cable |
| 2211100601 | Spare Battery rechargeable for C31XXi DECT handsets |

Accessoires



DECT Charger kit

Charger kit for C-31xx series DECT rough handsets. Includes Power Supply V3 100-230 Vac



Headset for dect handset

Rough with cable

Used With



IP DECT Base Station

IP Base Station for KWS6500



IP DECT Server 400 1G8

Version

Server Base Station