zenitel

DATASHEET

2210020000

Serveur d'alarme IP DECT

8 entrées d'alarme



Description

- Solution complète de messagerie et d'alarme
- Opérations permettant d'économiser du temps
- Sécurité opérationnelle améliorée
- Gestion efficace des combinés
- Facile à configurer, installer et utiliser
- Intégré avec la solution ACM DECT IP Vingtor-Stentofon
- Extensible jusqu'à 50 utilisateurs (licence de base)

Le serveur d'alarme IP DECT Vingtor-Stentofon est une plateforme de messagerie IP qui permet l'intégration d'un système d'alarme et de messagerie fiable et efficace avec la solution de communication DECT IP pour les navires. Le

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 10:53

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

serveur reçoit, gère et distribue les messages d'alarme. Il peut, par exemple, diffuser des informations cruciales telles que des alarmes moteur ou des alarmes incendie à bord du navire. Les messages d'alarme peuvent être distribué à un groupe de téléphones ou à un seul téléphone.

Le serveur d'alarme IP DECT Vingtor-Stentofon peut facilement être intégré avec la solution IP DECT Vingtor-Stentofon.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

GÉNÉRAL

SERVEUR	
Dimensions (HxLxP)	71 x 240 x 120 mm
Poids	3,8 kg
Alimentation	9-30 VDC / Max. = 36 W, Normalement = 20 W (la tension d’entrée ne doit pas dépasser 30 V)
Interface réseau	2 RJ45 Ethernet 10/100 Mbit/s
Capacité	Jusqu'à 14 2210020001(modules d'alarme), 112 alarmes au total
Températures de fonctionnement	De -15°C à +55°C
MODULE D'ALARME	
Dimensions (HxLxP)	120 x 30 x 75 mm
Poids	0,2 kg
Alimentation	24 VDC
Communication	RS485
Capacité	8 entrées opto
Entrée d'alarme	8 entrées de relais
Sortie d'alarme	DECT IP, Journal de l'imprimante, Fichier journal
Gestion et contrôle	112 alarmes différentes
	Outil de configuration sur navigateur Internet
	Messages textes avec 136 caractères
	15 signaux d’alarme

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 10:53

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company’s Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

	différents
	Temps de pause flexible de 0,1 à 2250 secondes
	Répétition des alarmes par intervalle de 1 à 2250 secondes

Used With



KWS400

Système serveur IP DECT KWS400

Référence Produit: 2211010200



KWS6500

Serveur IP DECT, 19" 1U, 110-240 VAC

Référence Produit: 2211000150

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.