

1007082000

Industrial Master Station

Noise Cancelling



Description

- ✓ Fully equipped master station with free access to all extensions and features
- ✓ Rugged waterproof and chip-resistant casing in orange makrolon
- ✓ Noise cancelling microphone with protective flange
- ✓ Red microphone live lamp
- ✓ Built-in 10W (8 Ohm) VOX operated power amplifier
- ✓ For use with external loudspeaker with or without power amplifier
- ✓ Screw terminals for easy connection of installation cables


This industrial master station is a waterproof model designed for humid, dirty and outdoor conditions. The station consists of a rugged splashproof and chip-resistant casing of orange makrolon and has a folio keyboard on the front. The front panel is hinged to the back casing to allow easy access during installation and service. The station has screw terminals with labels for easy installation. Two glands ensure waterproof and dustproof connection of

installation cable and loudspeaker wires.

The unit is equipped with a noise cancelling microphone preventing background noise from disturbing the conversation. A 20-70 Ohm external loudspeaker connects to the station or, alternatively, connect an 8-20 Ohm speaker for use with the built-in 10W (8 Ohm) VOX operated power amplifier. The external speaker must be placed at least one meter away from the station. The power amplifier requires separate 12V AC / 2 Amp power supply. The loudspeaker volume is adjustable with potentiometers located inside the casing and the station is programmable for permanent private mode by strap-plug setting inside the station.

The station is prepared for connection of a separate external handset.

Technical Dimensions



Specifications

MECHANICAL

| | |
|-------------------------|--|
| Operating Voltage | From exchange without power amp. 12 VAC / 2 Amp with power amp. |
| Cable Requirements | 2 pair 0.5 mm ² / 24 AWG twisted telephone cable. + 1 pair 0.8 mm ² / 20 AWG (to transformer if power amplifier is used) |
| Temperature | -50oC to +55oC |
| Relative humidity | 0% - 95% |
| Dimensions: (W x H x D) | 160 x 240 x 137 mm, 6.24" x 9.36" x 5.34" |
| Finish | Orange makrolon |
| Orange makrolon | 1.5 W (20 Ohm), 10W (8 Ohm) with power amplifier |
| Max. Loudspeaker Output | 20-70 Ohm without power amplifier, 8-20 Ohm with power amplifier |

| ORDER NUMBER | DESCRIPTION | SHIP WEIGHT |
|--------------|--|---------------------|
| 1007082000 | Noise Cancelling Industrial Master Station (external speaker is required) | 1.1 kg / 2 lb. 7 oz |
| Accessories: | | |
| VML-1520 | Horn Loudspeaker, 15 W/20 Ohm, IP-66 | 1.4 kg/3 lb |
| VMP-211 | Wall Mount Handset Unit (with PTT key), IP- 44 | 0.9 kg/2 lb |
| VMP-250 | Wall Mount Handset Unit /with PTT key), IP- 65 | 0.9 kg/2 lb |
| EOTRF 10115 | 220 VAC/12 VAC Mains Transformer (for power amplifier option) | 1.4 kg/3 lb |

GENERAL

| | |
|--|---------------------------|
| Frequency Range | 500-5000 Hz (\pm 8 dB) |
| Mic. Impedance for external handset | 200 - 600 Ohm |
| Connector Type | Screw terminals |
| Gland Diameter | 2 x PG9 |
| Indicator | LED (red) |

Accessories



VMP-36-PEL

Headset with Boom
Microphone and 10 Meter
Cable



VMP-36-PELP

Headset with Boom
Microphone, 10 Meter
Cable and Plug



CD-7-VMP

Plugbox Waterproof for
VMP-36-PELP



VMP-211

Wall Mounted Handset



VMP-250

Wall Mounted Handset
Waterproof



VML-1520

Horn Loudspeaker 15W, 20
OHM Waterproof



EHS-24O

Rotary Light 24V DC,
Orange



EHS-220O

Rotary Light 220VAC



Model-A

Telephone Booth



IRR-3

Relay Box