

2310102040

VERTILINE 166D

Power supply 19" 1HU 115/230Vac 16 ptc outputs max. 14A

DISCONTINUED

- ✓ Sixteen (16) individual power LEDs.
- ✓ Removable terminal blocks with locking screwflange.
- ✓ IEC 320 - 3-wire grounded line cord(detachable).
- ✓ 1HU, 19" rack mount

Description

Vertiline166D CCTV Rack Mount Power Supply provides 16 PTC protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.

Specifications

GENERAL

Size (WxHxD)	486 x 41 x 216 mm
Weight	7.0 kg
Power consumption	115 VAC: 460 VA, 240VAC: 600 VA

INPUT

Selectable 115VAC 60 Hz or 240VAC 50/60 Hz input
- 115VAC 60 Hz, 4 amp.
- 240VAC 50/60 Hz, 2.5 amp.

OUTPUT

Sixteen (16) individually selectable 24VAC or 28VAC power outputs with OFF position.
24VAC or 28VAC @ 14 amp max. total (0.875 amp per device, 2.5 amp max.).
Sixteen (16) PTC protected outputs rated @ 2.5 amp.
Main fuse rated @ 15 amp.
Surge suppression.

ELECTRICAL

Operating temperature	0° C to 49° C ambient
BTU/Hr	24VAC: 172.0 BTU/Hr // 28VAC: 200.63 BTU/Hr