

2220050009

J9625A

HP ProCurve 2620-24 PoE+ 24-port 10/100 PoE+



Description

The HP 2620 Switch Series provides cost-effectiveness, flexibility, and ease of use for enterprise edge, SMB, and branch office access layer deployments. This Fast Ethernet switch has a robust Basic Layer 3 feature set with static and RIP routing, PoE+, ACLs, sFlow, IPv6, and requires no software licensing.

The HP 2620 Switch Series can be managed with the optional HP Intelligent Management Center (IMC) Software for a single view of your entire network.

Specifications

The HP 2620-24-PoE+ Switch is a managed 28-port switch with 24 auto-sensing 10/100 ports capable of supporting PoE and 2 10/100/1000BASE-T ports and 2 SFP ports

ENVIRONMENT

Operating temperature	32°F to 131°F (0°C to 55°C)
Operating relative humidity	15% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS ~~100%~~ ENEC MIERCOM CERTIFIED GREEN AWARD

Frequency	50/60 Hz
Maximum heat dissipation	270 BTU/hr (284.85 kJ/hr), switch only: 270 BTU/hr; combined switch + max. PoE devices: 1751 BTU/hr
AC voltage	100 - 127/200 - 240 VAC
Current	4.9/2.5 A
Maximum power rating	428 W
Idle power	22.8 W
PoE capability	382 W PoE+

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	443 x 368.3 x 43.9 mm
Weight	4.84 kg
Mounting	Rack Mountable, 1HU

Accessories



J4858C

HP X121 1G SFP LC SX
MultiMode fiber - IEC60945
Compliant



J4860C

HP X121 1G SFP LC LH
Transceiver - SingleMode
fiber



J4859C

HP X121 1G SFP LC LX
Transceiver - SMF or MMF



J8177C

HP X121 1G SFP RJ45 T
Transceiver