

2220011122

J9727A

HP 2920-24G PoE+ - 20 PoE+ port 10/100/1000 + 4xRJ45/SFP



Description

The HP 2920 Switch Series provides security, scalability, and ease of use for enterprise edge, SMB and branch office, access-layer deployments. A powerful HP Networking ASIC delivers low latency, more packet buffering, and adaptive power consumption.

This robust Basic Layer 3 switch series supports modular stacking, 10GbE, RIP routing, PoE+, ACLs, sFlow, and IPv6. The HP 2920 Switch Series can be managed with the optional HP Intelligent Management Center (IMC) software for a single view of your entire network and is ready for the Software-defined Network (SDN) with OpenFlow support.

Specifications

The HP 2920-24G PoE+ Switch is a managed 24-port switch with 20 auto-sensing 10/100/1000 PoE+ ports and 4 dual-personality 10/100/1000 ports

ENVIRONMENT

Operating temperature	32°F to 131°F (0°C to 55°C)
Operating relative humidity	15% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	358 BTU/hr (377.69 kJ/hr)
AC voltage	100 - 240 VAC
Maximum power rating	475 W
Idle power	42 W
PoE power	370 W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	442.5 x 336 x 44 mm
Weight	5.46 kg
Mounting	Rack Mountable, 1HU

Accessories









J9731A

HP 2920 2-port 10GbE SFP+ Module

J4858C

HP X121 1G SFP LC SX MultiMode fiber - IEC60945 Compliant

J4860C

HP X121 1G SFP LC LH Transceiver - SingleMode fiber J4859C

HP X121 1G SFP LC LX Transceiver - SMF or MMF

page 2/3



J8177C

HP X121 1G SFP RJ45 T Transceiver

page 3/3