

2220011123

J9729A

HP 2920-48G - PoE+ - 44 PoE+ port 10/100/1000 + 4xRJ45/SF



Description

The HP 2920 Switch Series provides security, scalability, and ease of use for enterprise edge, SMB and branch office, access-layer deployments. A powerful HP Networking ASIC delivers low latency, more packet buffering, and adaptive power consumption.

This robust Basic Layer 3 switch series supports modular stacking, 10GbE, RIP routing, PoE+, ACLs, sFlow, and IPv6. The HP 2920 Switch Series can be managed with the optional HP Intelligent Management Center (IMC) software for a single view of your entire network and is ready for the Software-defined Network (SDN) with OpenFlow support.

Specifications

48-port basic L3 10/100/1000 PoE+ switch with 2 slots for optional 10G modules, 1 slot for optional stacking module and a modular power supply

ENVIRONMENT

Operating temperature	32°F to 131°F (0°C to 55°C)
Operating relative humidity	15% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	399 BTU/hr (420.95 kJ/hr)
AC voltage	100 - 240 VAC
Maximum power rating	487 W
Idle power	46 W
PoE power	370 W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	442.5 x 336 x 43.9 mm
Weight	5.7 kg
Mounting	Rack Mountable, 1HU

Accessories



J9731A

HP 2920 2-port 10GbE SFP+ Module

Item Number: 2220011156



J4858C

HP X121 1G SFP LC SX MultiMode fiber - IEC60945 Compliant

Item Number: 2220011150



J4860C

HP X121 1G SFP LC LH Transceiver - SingleMode fiber

Item Number: 2220011151



J4859C

HP X121 1G SFP LC LX Transceiver - SMF or MMF

Item Number: 2220011152



J8177C

HP X121 1G SFP RJ45 T
Transceiver

Item Number: 2220010016