

2220011153

# J9150A

HP X132 10G SFP+ LC SR Transceiver - MultiMode fiber



### Description

A 10-Gigabit transceiver in SFP+ form-factor that supports the 10-Gigabit SR standard, providing 10-Gigabit connectivity up to 300 m on multimode fiber.

# **Specifications**

#### **CABLING**

Туре	62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively	
Maximum distance	2-26m with 62.5 μm multimode cable @ 160 MHz*km	
	2-33m with 62.5 μm multimode cable @ 200 MHz*km	
	2-66m with 50 μm multimode cable @ 400 MHz*km	
	2-82m with 50 μm multimode cable @ 500 MHz*km	
	2-300m with 50 μm multimode cable @ 2000 MHz*km	

### **ENVIRONMENT**

Operating temperature	32°F to 158°F (0°C to 70°C)
Operating relative humidity	0% to 85%, noncondensing

#### **DIMENSIONS & WEIGHT**

Dimensions (W x D x H)	13.8 x 55.7 x 11.9 mm
Weight	0.02 kg

page 2/2