

2220050008

ProCurve 2620-24/DNV

HP ProCurve 2620-24 PoE+ Ethernet Switch Kit - IEC60945 Compliant



Description

The HP 2620 Switch Series provides cost-effectiveness, flexibility, and ease of use for enterprise edge, SMB, and branch office access layer deployments. This Fast Ethernet switch has a robust Basic Layer 3 feature set with static and RIP routing, PoE+, ACLs, sFlow, IPv6, and requires no software licensing.

The HP 2620 Switch Series can be managed with the optional HP Intelligent Management Center (IMC) Software for a single view of your entire network.

IEC60945 Compliant, DNV Type approved for EXIGO and ACM systems

Specifications

The HP 2620-24-PoE+ Switch is a managed 28-port switch with 24 auto-sensing 10/100 ports capable of supporting PoE and 2 10/100/1000BASE-T ports and 2 SFP ports.

Includes AC filter, 1-phase, 3A, 250VAC, Din-Rail Mount

ENVIRONMENT

Operating temperature	32°F to 131°F (0°C to 55°C)
Operating relative humidity	15% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS ACHIEVED MIERCOM CERTIFIED GREEN AWARD

Frequency	50/60 Hz
Maximum heat dissipation	270 BTU/hr (284.85 kJ/hr), switch only: 270 BTU/hr; combined switch + max. PoE devices: 1751 BTU/hr
AC voltage	100 - 127/200 - 240 VAC
Current	4.9/2.5 A
Maximum power rating	428 W
Idle power	22.8 W
PoE capability	382 W PoE+

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	443 x 368.3 x 43.9 mm
Weight	4.84 kg
Mounting	Rack Mountable, 1HU