

2220050007

## 3560X-24P-S

CISCO Catalyst 3560X 24-port 10/100/1000 PoE+ IP Base



---

## Description

The Cisco Catalyst 3560-X Series Switches are an enterprise-class lines of stackable and standalone switches, respectively. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features, IEEE 802.3at Power over Ethernet Plus (PoE+) configurations, optional network modules, redundant power supplies, and Media Access Control Security (MACsec) features. The Cisco Catalyst 3560-X enhance productivity by enabling applications such as IP telephony, wireless, and video for borderless network experience.

# Specifications

The Cisco Catalyst 3560-X is managed 24-port switch with 24 auto-sensing 10/100 ports capable of supporting PoE and IP Base feature set.

## ENVIRONMENT

Operating temperature	23 to 113°F (-5 to 45°C)
Operating relative humidity	5% to 95%, noncondensing

## ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	2465 BTU/hr
AC voltage	100 / 240 VAC
Current	10 / 5 A
Maximum power rating	715 W (with 2 PSU)
Available PoE Power	435W

## DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 460 x 44.5 mm
Weight	7.1 kg
Mounting	Rack Mountable, 1HU

# Accessories



### C3KX-NM-10G

10GbE uplink module - 2xSFP+ and 2x SFP ports for 3560X, 3750X



### GLC-SX-MMD

Cisco 1000Base-SX SFP Transceiver Module for MultiMode Fiber - IEC60945 Compliant



### GLC-ZX-SMD

Cisco 1000BASE-ZX SFP transceiver module for Single-Mode fiber



### GLC-LH-SMD

Cisco 1000BASE-LH-SMD SFP for Single-Mode Fiber



#### GLC-T

Cisco 1000BASE-T SFP 1G RJ-45 for Copper Networks



#### SFP-10G-SR

CISCO 10GBase-SR SFP+ 10GbE transceiver module for Multimode fiber



#### SFP-10G-LRM

CISCO 10GBase-LRM SFP+ 10GbE transceiver module for both multimode and single-mode fibers



#### SFP-10G-LR

CISCO 10GBase-LR SFP+ 10GbE transceiver module for single-mode fibers