

2220012126

## 3750X-12S-E

Cisco Catalyst 3750X-12S-E 12 port SFP switch IP Services



---

## Description

The Cisco Catalyst 3750-X Series Switches are an enterprise-class lines of stackable and standalone switches, respectively. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features, optional network modules, redundant power supplies, and Media Access Control Security (MACsec) features. The Cisco Catalyst 3750-X enhance productivity by enabling applications such as IP telephony, wireless, and video for borderless network experience.

# Specifications

The Cisco Catalyst 3750-X is managed 12-port switch with 12 auto-sensing 1Gbit Ethernet SFP ports and IP Services feature set

## ENVIRONMENT

Operating temperature	23 to 113°F (-5 to 45°C)
Operating relative humidity	5% to 95%, noncondensing

## ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	1207 BTU/hr
AC voltage	100 / 240 VAC
Current	4 / 2 A
Maximum power rating	350 W

## DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 460 x 44.5 mm
Weight	6.8 kg
Mounting	Rack Mountable, 1HU

# Accessories



### GLC-SX-MMD

Cisco 1000Base-SX SFP Transceiver Module for MultiMode Fiber - IEC60945 Compliant



### GLC-ZX-SMD

Cisco 1000BASE-ZX SFP transceiver module for Single-Mode fiber



### GLC-LH-SMD

Cisco 1000BASE-LX/LH SFP for Both Multimode and Single-Mode Fibers



### GLC-T

Cisco 1000BASE-T SFP 1G RJ-45 for Copper Networks



#### SFP-10G-SR

CISCO 10GBase-SR SFP+  
10GbE transceiver module for  
Multimode fiber



#### SFP-10G-LRM

CISCO 10GBase-LRM SFP+  
10GbE transceiver module for  
both multimode and single-mode  
fibers



#### SFP-10G-LR

CISCO 10GBase-LR SFP+  
10GbE transceiver module for  
single-mode fibers