

2220012125

3750X-24S-S

Cisco Catalyst 3750X-24S-S 24 port SFP switch IP Base



Description

The Cisco Catalyst 3750-X Series Switches are an enterprise-class lines of stackable and standalone switches, respectively. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features, optional network modules, redundant power supplies, and Media Access Control Security (MACsec) features. The Cisco Catalyst 3750-X enhance productivity by enabling applications such as IP telephony, wireless, and video for borderless network experience.

Specifications

The Cisco Catalyst 3750-X is managed 24-port switch with 24 auto-sensing 1Gbit Ethernet SFP ports and IP Base feature set.

ENVIRONMENT

Operating temperature	23 to 113°F (-5 to 45°C)
Operating relative humidity	5% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	1207 BTU/hr
AC voltage	100 / 240 VAC
Current	4 / 2 A
Maximum power rating	350 W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 460 x 44.5 mm
Weight	7 kg
Mounting	Rack Mountable, 1HU

Accessories



GLC-SX-MMD

Cisco 1000Base-SX SFP
Transceiver Module for
MultiMode Fiber - IEC60945
Compliant



GLC-ZX-SMD

Cisco 1000BASE-ZX SFP
transceiver module for Single-
Mode fiber



GLC-LH-SMD

Cisco 1000BASE-LX/LH SFP
for Both Multimode and Single-
Mode Fibers



GLC-T

Cisco 1000BASE-T SFP 1G
RJ-45 for Copper Networks



SFP-10G-SR

CISCO 10GBase-SR SFP+
10GbE transceiver module for
Multimode fiber



SFP-10G-LRM

CISCO 10GBase-LRM SFP+
10GbE transceiver module for
both multimode and single-
mode fibers



SFP-10G-LR

CISCO 10GBase-LR SFP+
10GbE transceiver module for
single-mode fibers