

2220012064

**2960+24PC-L**

CISCO CATALYST C2960+24PC-L ETHERNET SWITCH

**DISCONTINUED**

---

## Description

The Cisco Catalyst 2960-Plus Series Switches are fixed-configuration Fast Ethernet switches that provide enterprise-class Layer 2 switching for branch offices, conventional workspaces, and infrastructure applications. They enable reliable and secure operations with lower total cost of ownership through a range of Cisco IOS software features, including Cisco Catalyst SmartOperations.

# Specifications

The Cisco 2960+24PC-L is managed 24-port switch with 24 auto-sensing 10/100 ports capable of supporting PoE and 2 Gigabit Ethernet combo ports.

## ENVIRONMENT

|                             |                           |
|-----------------------------|---------------------------|
| Operating temperature       | 23° to 113°F (-5°to 45°C) |
| Operating relative humidity | 10% to 95% noncondensing  |

## ELECTRICAL CHARACTERISTICS

|                          |                             |
|--------------------------|-----------------------------|
| Frequency                | 50/60 Hz                    |
| Maximum heat dissipation | 1400                        |
| AC voltage               | 100 / 240 VAC               |
| Current                  | 4 / 2 A                     |
| Maximum power rating     | 410 W                       |
| Available PoE Power      | 370W (24 ports up to 15.4W) |

## DIMENSIONS & WEIGHT

|                        |                     |
|------------------------|---------------------|
| Dimensions (W x D x H) | 450 x 332 x 44 mm   |
| Weight                 | 5.4 kg              |
| Mounting               | Rack Mountable, 1HU |