

2220012065

## 2960+48PST-L

CISCO CATALYST C2960+48PST-L ETHERNET SWITCH



---

---

## Description

The Cisco Catalyst 2960-Plus Series Switches are fixed-configuration Fast Ethernet switches that provide enterprise-class Layer 2 switching for branch offices, conventional workspaces, and infrastructure applications. They enable reliable and secure operations with lower total cost of ownership through a range of Cisco IOS software features, including Cisco Catalyst SmartOperations.

# Specifications

The Cisco 2960+24PC-L is managed 48-port switch with 48 auto-sensing 10/100 ports capable of supporting PoE, 2 Gigabit Ethernet RJ45 ports and 2 Gigabit Ethernet SFP ports.

## ENVIRONMENT

Operating temperature	23° to 113°F (-5°to 45°C)
Operating relative humidity	10% to 95% noncondensing

## ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	1400
AC voltage	100 / 240 VAC
Current	4 / 2 A
Maximum power rating	420 W
Available PoE Power	370W (24 ports up to 15.4W)

## DIMENSIONS & WEIGHT

Dimensions (W x D x H)	450 x 332 x 44 mm
Weight	5.4 kg
Mounting	Rack Mountable, 1HU