

2220012129

## 2960X-48LPS-L

CISCO Catalyst 2960X 48-port 10/100/1000 PoE+ Switch



---

## Description

Cisco Catalyst 2960-X Series Switches are fixed-configuration, stackable Gigabit Ethernet switches that provide enterprise-class access for campus and branch applications. Designed for operational simplicity to lower total cost of ownership, they enable scalable, secure and energy-efficient business operations with intelligent services and a range of advanced Cisco IOS Software features.

# Specifications

The Cisco 2960X-48LPS-L is managed 48-port switch with 48 auto-sensing 10/100/1000 PoE+ ports and 4 Gigabit Ethernet SFP ports.

## ENVIRONMENT

Operating temperature	23° to 113°F (-5°to 45°C)
Operating relative humidity	10% to 95% noncondensing

## ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	1470.63 BTU/hr
AC voltage	100 / 240 VAC
Current	5 / 2 A
Maximum power rating	431 W
Available PoE power	370 W (12 ports up to 30W or 24 ports up to 15.4W)

## DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 368 x 45 mm
Weight	5.8 kg
Mounting	Rack Mountable, 1HU