

2220012319

# CISCO SIP to SIP Gateway

CISCO SIP to SIP Gateway with 10 trunk license



# Description

Cisco 2900 Series Integrated Services Routers offer embedded hardware encryption acceleration, voice- and video-capable digital signal processor (DSP) slots, optional firewall, intrusion prevention, call processing, voicemail, and application services. In addition, the platforms support the industries widest range of wired and wireless connectivity options such as T1/E1, T3/E3, xDSL, copper and fiber GE.

Cisco IOS® Software Universal image is installed on each ISR G2. The Universal image contains all of the Cisco IOS technology sets which can be activated with a software license. This allows your business to quickly deploy advanced features without downloading a new IOS image. Additionally, larger default memory is included to support the new capabilities.

# **Specifications**

\* 10x SIP to SIP trunk license

#### **ENVIRONMENT**

Operating temperature	32 to 104°F (0 to 40°C)
Operating relative humidity	10% to 85% noncondensing

## **ELECTRICAL CHARACTERISTICS**

Frequency	47 to 63 Hz
Maximum heat dissipation	511.82 BTU/hr
AC voltage	100 / 240 VAC
Current	1.5 / 0.6 A
Maximum power rating	150 W

#### **DIMENSIONS & WEIGHT**

Dimensions (W x D x H)	438.2 x 439.4 x 44.5 mm
Weight	6.1 kg
Mounting	Rack Mountable, 1HU

# Accessories









VWIC3-1MFT-T1/E1

Cisco 1-Port T1/E1 Multiflex Trunk Voice/WAN Interface Crd VIC2-2BRI-NT/TE

Cisco Two-port Voice Interface Card - BRI (NT and TE) VIC2-4FXO

Cisco Four-Port Voice Interface Card - FXO (VIC2-4FXO) VIC3-4FXS/DID

Cisco Four Port Voice Interface Card - FXS and DID

page 2/3

www.zenitel.com info@zenitel.com

Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.









## EHWIC-3G-HSPA+7

Cisco 3G HSPA+7 with GPS based MC8705

## EHWIC-4G-LTE-G

Cisco 4G LTE EHWIC for Global 800/900/1800/2100/2600 MHz

#### PVDM3-16U32

Cisco PVDM3-16U32 16 to 32-channel factory upgrade

## FL-CUBEE-5

Cisco Unified Border Element Enterprise License - 5 sessions



#### SL-29-DATA-K9

Cisco Data License for Cisco 2901-2951



# SL-29-UC-K9

Cisco Unified Communications License for Cisco 2901-2951



### SL-29-SEC-K9

Cisco Security License for Cisco 2901-2951



### FL-CME-SRST-5

CISCO Communication Manager Express or SRST-5 seat license



### FL-CME-SRST-25

CISCO Communication Manager Express or SRST-25 seat license

page 3/3