

3006100087

VES-360TF

Loudspeaker 6W, Flush Mounted, 3" Element



Product image
not available

Description

- ✓ Flush mounting
- ✓ Steel back box to reduce fire risk and spread
- ✓ With 100V line transformer
- ✓ Adjustable power tapping: 0,5W - 1,5W - 3,0W - 6,0W
- ✓ Lead cable through cable gland
- ✓ Install the steel box into the cut-out hole with 2 screws
- ✓ If 70V, replace red cable with the green cable in the terminal
- ✓ Connect to terminal and select required tapping

- ✓ Install loudspeaker baffle to wall / ceiling by means of 2 screws. Screw loudspeaker grill gently until it stops
- ✓ For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated
- ✓ Do not open loudspeaker when energized

Specifications

GENERAL

Material / Color	Steel, alu. grill / RAL9010
Mounting	4 (2 + 2) screws
Termination	Ceramic terminals
Weight w/transformer	0.7 kg
IP-rating	NA
Max. / min. amb. temp	120 °C / -20 °C
Rated / max. power	6 W / 8 W
SPL 1W/1m	88 dB
SPL rated power	95 dB
Effective freq. range	220 – 20000 Hz
Dispersion (-6dB) 1kHz / 4kHz	145° / 90°
Directivity factor, Q	6,8
Options	Impedances, colors, labels

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3006100087	LOUDSPEAKER 6W, FLUSH MOUNTED, 3" ELEMENT	0.7 KG