

2211100515

## Dect EX Handset

With Belt Clip

DISCONTINUED PRODUCT, NO LONGER AVAILABLE.



## Description

This item is EOL from the manufacturer and no longer available

- ✓ Ultimate handset for hazardous environments built for long-term dependability
- ✓ ATEX and IEC approved according to European and international standard
- ✓ Very high battery capacity
- ✓ Telephone book with room for 200 numbers
- ✓ Rough and office headset options for hands-free usage and noise reduction
- ✓ Large alphanumeric, back-lit display
- ✓ Volume control and LED indication of incoming and unanswered calls

The IP DECT Handset, EX is the ultimate handset for environments with potentially explosive conditions and is built for long-term dependability in harsh environments. A robust, well designed and full feature handset, it meets the

demands for easy mobility. The handset is ideal for potentially explosive work environments, such as oil, gas and chemical production as well as dust-filled environments. In order to meet special requirements, the handset is IP64 classified, which means that it is dust tight and protected against splashing water.

The handset has a very high battery capacity with speech/stand by time > 15/150 hours. The handset is easy to use with large backlit display. The display provides calling information (Calling number presentation) as well as phonebook, call history and phone setting.

The phones can be equipped with noise cancelling headsets to provide comfortable usage in noisy environments. Optionally office type headset can be used to provide hands-free operations in other environments. A wide set of accessories can be provided for comfortable wear and usage of phone – like charger, belt clip, leather poach handle.

Each DECT phone requires a SIP user license in the ACM System.

# Specifications

| ORDER NUMBER | DESCRIPTION   | SHIP WEIGHT |
|--------------|---|-------------|
| 2211100515   | DECT Handset Ex –<br>IP64 Require One Sip<br>Station License In ACM | 0,13 Kg     |
| 2211100215   | Ex Handset Charger  | 0,01 Kg     |
| 2211100605   | Battery For DECT EX   | 0,04 Kg     |
| 2211100700   | Belt Clip For DECT<br>Rough & Ex                                    | 0,10 Kg     |
| 2211100702   | Leather Pouch, Belt Clip<br>For DECT Rough & Ex                     | 0,10 Kg     |
| 2221100707   | Leather Pouch, Handle<br>For DECT Rough & Ex                        | 0,10 Kg     |
| 2211200101   | Headset For DECT<br>Handset Rough & Ex                              | 0,31 Kg     |
| 2211200111   | Cable For Headset For<br>DECT Handset Rough<br>& Ex                 | 0,05 Kg     |

## GENERAL

|                    |  |
|--------------------|--|
| Dimensions (LxWxH) | 148x50x28 mm   |
| Environment        | IP64 (dust tight and water resistant)  |
| Weight             | 130g (including battery)   |
| Environment        | IP64 (dust tight and water resistant)  |
| Menu language      | UK, DE, FR, IT, ES, NL, PT, SV, DA, NO   |
| Environment        | IP64 (dust tight and water resistant)  |
| Battery capacity   | >15/150 hours (speech/standby)   |
| Display            | Alphanumeric, backlit  |
| Menu language      | UK, DE, FR, IT, ES, NL, PT, SV, DA, NO   |
| Phonebook          | 200 entries  |
| Features           | Vibrate and silent mode<br>Auto answer Loud speaking LED indication of incoming and unanswered calls<br>Volume control Call history Calling number presentation (CLIP) |
| Power (charger)    | 110-230 VAC  |
| Radio              | DECT GAP Handover and roaming between base stations Dynamic channel selection and allocation Repeater support Encrypted radio  |
| Radio frequency    | 1881.792-1897.344 MHz (License free band Europe)   |
| ATEX approved      | II2G II3D T60°C EEx ib IIC T3  |
| IEC approved       | Ex ib IIC T3   |

# Accessories



## Charger kit EX

Charger for dect handset  
EX 110 - 230V ac

Item Number: 2211100562



## Light mono headset EX

W/ hook switch

Item Number: 2211200102