



1023253008

EBMDR-8

Exigo Button Expansion Module, 8 Buttons

- Button expansion module for ECPIR-x
- Powered from ECPIR-x
- Eight programmable buttons with individual labels and status indicators
- Optional button protection covers
- Four units can be connected to one access panel



Description

The EBMDR-8 button expansion module is developed for expanding the button capacity of the ECPIR-x access panels or intercom. Each button features eight fully programmable buttons that can be used to manually initiate alarms, select zones, or any other action in the Exigo system.


Each of the module's buttons features two independent indicators that show the status of the button's function. Up to four EBMDR-8 button expansion modules can be daisy chained to one console panel.

Technical Dimensions

www.zenitel.com

info@zenitel.com


Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.




D

h

2000







0

page 2/4

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

MECHANICAL

Dimensions (HxWxD):	144 x 96 x 41.5 mm
Weight:	500 g

ENVIRONMENTAL

Operating temperature:	-10°C to +60 °C
Operating humidity:	10% to 95% (non- condensing)
Storage temperature:	-40°C to +70°C
Storage humidity:	10% to 95% (non- condensing)
Air pressure:	600 hPa to 1300 hPa
IP rating:	IP-32
Magnetic Compass Safe Distance	60 cm
IEC 60945 Environmental Category	Protected
Operator & Reading Distance	0,71 m

CERTIFICATIONS

Immunity: EN 60945, EN 50130-4, EN 61000-6-1, EN 61000-6-2, EN 55103-2, FCC-47 part 15B Emissions: EN 60945, EN 50130-4, EN 61000-6-3, EN 61000-6-4, EN 55103-1, FCC-47 part 15B Safety: UL 60950-1, cUL 60950-1, CB to IEC 60950-1			
Emissions: 61000-6-3, EN 61000-6-4, EN 55103-1, FCC-47 part 15B Safety: UL 60950-1, cUL 60950-1,	Immunity:	61000-6-1, EN 61000-6-2, EN 55103-2, FCC-47 part	
Safety	Emissions:	61000-6-3, EN 61000-6-4, EN 55103-1, FCC-47 part	
	Safety:		

Accessories

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.



EMBR-1

Mounting Box for ECPIR, EAPIR and EBMDR-8 Panels



Mounting Box for ECPIR, EAPIR and EBMDR-8 Panels



Mounting plate for Exigo Access Panels - 2

Mounting plate for 2 pcs. Exigo Access Panel, 19" 4HU



Mounting plate for Exigo Access Panels - 3

Mounting plate for 3 pcs. Exigo Access Panel, 19" 4HU

Used With



ECPIR-3P

Exigo Access Panel / Turbine Intercom



ECPIR-P

Exigo Call Panel, PTT Button



EAPIR-8

EXIGO Alarm Panel, 8 buttons

page 4/4

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.