



2340032005

DA-P 20-130/T-EN54

EN54 projector speaker 20 watt

- Quick mounting
- High impact ABS plastic

Description

Sturdy soundprojector for voice alarm applications, certified according to EN 54-24, suitable for voice announcements and background music with excellent sound quality in buildings.

The 20W powered speaker is equipped with a 130mm full-range loudspeaker and a 100V line transformer with 4 power adjustments. A robust ABS plastic housing in white and a solid aluminium mounting bracket ensures the permanent installation of this speaker.

For additional reliability, a 2 pin-ceramic block and a thermal fuse are provided in a junction box and the speaker chassis is impregnated against wetness.

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

CHARACTERISTICS	VALUE
Power	20/10/5/2,5 W
Frequency Range	150 - 20.000 Hz
Frequency Response	120 - 21.000 Hz
SPL 1W/1m, peak	99,5 dB
SPL , 1W/4m, peak	83,7 dB
SPL Pmax/4m, peak	96,7 dB
InformationSensitivity EN54-24, 1W/4m	75,0 dB
Dispersion -6dB, 500Hz	360°
Dispersion -6dB, 1KHz	252°
Dispersion -6dB, 2KHz	110°
Dispersion -6dB, 4KHz	58°
Connector	2-pin ceramic block
Maximum cable cross section	8mm²
Max. cable cross section loop	2x2mm²
Temperature range	-20 / +90°
Dimensions	145 x 222mm
IP Rating	IP66
Weight (net)	1,45kg
Colour	white
Mounting	Mounting bracket
Certificate Number	1438/CPR/0388