



2340032008

DK 30/T-EN54

EN54 horn speaker 30 watt

REPLACEMENT ITEM 2340032011 DK 30/T-EN54-

- High sound pressure level
- Weather proof

Description

Weatherproof horn speaker for voice alarm applications, certified according to EN 54-24, suitable for industrial indoor and outdoor use with high sound pressure level.

The 30W powered speaker is equipped with a 100V line transformer with 4 power adjustments, also low-impedance operation (20ohm) is possible. The impact-resistant ABS housing UL94V0 in RAL 7035 guarantees long-term stability. For additional reliability, a ceramic block and a thermal fuse is provided in a junction box.

The speaker is also secured with the high protection class IP 66 against the security risks of environmental influences.

Included is a U-shaped, stainless steel universal mount for flexible installation.

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

CHARACTERISTICS	VALUE
Power	30/20/10/5 (20) W
Frequency Range	592 - 6.900 Hz
Frequency Response	250 - 15.000 Hz
SPL 1W/1m, peak	110,1 dB
SPL , 1W/4m, peak	98,1 dB
SPL Pmax/4m, peak	112,8 dB
Sensitivity EN54-24, 1W/4m	79,9 dB
Dispersion -6dB, 500Hz	360°
Dispersion -6dB, 1KHz	103°
Dispersion -6dB, 2KHz	62°
Dispersion -6dB, 4KHz	32°
Connector	ceramic block
Maximum cable cross section	8mm ²
Max. cable cross section loop	2x2mm²
Temperature range	-20 / +90 °C
Dimensions	235x303 mm
IP Rating	IP66
Weight (net)	2,17 kg
Colour	RAL 7035
Mounting	Mounting bracket
Certificate Number	1438/CPR/0242