

2211100519

C3115i DECT handset rough

including belt clip





Man down



Onboard communication

Description

- Water and dust resistant according to IP-65.
- Large 1.8" display, 7 lines with color-coding Dynamic display with up to 16 characters ineach line, each message can contain 198 characters.
- Built-in vibrator for noisy environments or discretion is required.
- High battery capacity LI-lon battery.
- 2.5 mm jack for headset.
- Loud speaking and hands free function.
- Battery and belt clip included.
- A large dedicated alarm button on the top of the handset makes it easy to call for help.
- 🕢 Extra function key on the right side. This is used for alarm acknowledge, send soft alarms or to call colleagues.
- Supports advanced alarm handling which contains symbols, color-code, priority, alarm ID, dynamic alarm list, extended

page 1/4

alarm list and automatic alarms. Equipped with man down and motion alarm, for monitoring of movement or non movement.

Pull cord alarm is ideal for protection against theft, personal attack or for use in distress situations

Specifications

GENERAL

Size (WxHxD)	152 x 53 x 27 mm
Weight	0.138 kg
Display	1,8" 65 000 colors
Operational temperature	0-40°C
Speech/ standby time	16/150h
Ingress protection	IP65
Headset interface	2,5mm jack plug
Built-in vibrator	Yes
Menu languages	Swedish, English, Danish, German, French, Dutch, Finnish, Norwegian, Spanish, Czech, Polish, Portuguese and Italian
Radio frequency	EMEA, 1881.792- 1897.344 MHz

ACCESSORIES

2211100560	Charger and Power Cable
9021804001	Charger C-31xx w/ port for USB programming with power supply
2211100706	Leather case incl. belt clip adapter
2211100711	Fixed belt clip, grey
2211100703	Spare Belt clip ("Swivel")
2211100601	Spare Battery rechargeable for C31XXi DECT handsets
9021801000	Microphone for DECT handset C-31xx

Accessories

page 3/4



DECT Charger kit

Charger kit for C-31xx series DECT rough handsets. Includes Power Supply V3 100-230 Vac



Headset for DECT handset V2

Headset

Used With



IP DECT Base Station

IP Base Station for KWS6500



IP DECT Server 400 1G8

Version

Server Base Station