

2340130002

SPA-V2-REDUNDANT

PA/GA REDUNDANT Main Unit, 19" RACK



Description

The SPA-V2-REDUNDANT is part of the SPA-V2 series public address and general alarm system combines quality and value. The SPA-V2 is an improved second generation system which in first generation version has been installed in thousands of ships around the world.

GENERAL:

- ✓ Input & priorities for 3 microphone panels
- ✓ Input from talk-back system
- ✓ Input from entertainment system
- ✓ PABX Input with zone presets
- ✓ 6 zones 100 V signal output
- ✓ Input for 2 alarm panels
- ✓ 2x Fire alarm input, all call and zone selection (fire crew)

- ✓ Alarm mute during PA message

SPA-V2-REDUNDANT is a single 16HU cabinet with full A-B redundancy PAGA system.

INCLUDES:

- ✓ 2x SPA-TERMINALBOARD-V2
- ✓ 2x SPA-EE3-V2 ALARM GENERATOR
- ✓ 2x SPA-AL-REL-V2
- ✓ 2x AC/DC PSU
- ✓ 2x WIRING PREPARED FOR VPA AMPLIFIERS

NOTE: Dual access panels must be used for connection and correct redundancy functionality.

NOTE: Add 2x VPA amplifiers to SPA-V2-REDUNDANT. For more than 2 amplifiers; add 2x SPA-MUL-V2 and SPA-EXPW (Rack expansion w/ wiring).

Technical Dimensions

Dimensions to be specified.

Specifications

GENERAL

Rack size (WxHxD)	525 x 780 x 525 mm (19" 16HU)
Material	Black painted steel
Mounting	Floor
Voltage input	Mains 230 VAC & 24 VDC
Connections	Plugable terminals for max. 2.5mm ² cable
Cable requirements	Signal cable 0.75mm ² twisted outer screen
Amplifier	None. Prepared for 2x VPA amplifier up to 400W
Output	N/A
Operating temperaure	-20 - +55°C
Relative humidity	<95%
Safety	EN 60065
Tested according	EN 60945