

2220012131

3850-12S-S

Cisco Catalyst 3850-12S-S 12 port SFP switch

DISCONTINUED

Description

The Cisco Catalyst 3850 Series Switches are an enterprise-class lines of stackable and standalone switches, respectively. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features, optional network modules, redundant power supplies, and Media Access Control Security (MACsec) features. The Cisco Catalyst 3850 enhance productivity by enabling applications such as IP telephony, wireless, and video for borderless network experience.

Specifications

The Cisco Catalyst 3850-12S-S is managed 12-port switch with 12 auto-sensing 1Gbit Ethernet SFP ports and IP Base feature set

ENVIRONMENT

Operating temperature	23 to 113°F (-5 to 45°C)
Operating relative humidity	10% to 95%, noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	1207 BTU/hr
AC voltage	100 / 240 VAC
Current	4 / 2 A
Maximum power rating	350 W

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 450 x 44.5 mm
Weight	7.02 kg
Mounting	Rack Mountable, 1HU

Accessories



GLC-SX-MMD

Cisco 1000Base-SX SFP
Transceiver Module for
MultiMode Fiber - IEC60945
Compliant



GLC-LH-SMD

Cisco 1000BASE-LH-SMD
SFP for Single-Mode Fiber



SFP-10G-SR

CISCO 10GBase-SR SFP+
10GbE transceiver module
for Multimode fiber



SFP-10G-LRM

CISCO 10GBase-LRM
SFP+ 10GbE transceiver
module for both multimode
and single-mode fibers



C3850-NM-2-10G

Cisco Catalyst 3850 4x
1Gbit or 2x 10GE Network
Module