zenitel

DATASHEET



2200012004

GXP-2200EXT

Expansion Module for GXP-2170 IP Phones

- 128x384 backlit LCD display
- 20 programmable dual-color buttons
- BLF/speed dial
- Daisy-chain up to 4 modules for up to 160 contacts/extensions

Description

The GXP-2200EXT delivers additional functionality, versatility and flexibility to GXP-2170 Enterprise IP Phones. The GXP-2200EXT module features a large 128 x 384 graphic LCD and 20 programmable buttons (each with dual color LED). It offers up to 40 extensions per module by using the 2 page switch keys and up to 160 buttons when 4 extension modules are daisy-chained together. This extension module is connected, powered, and controlled by the host phone to provide the benefit of additional extension keys instantly.

GXP-2200EXT supports the traditional call features on each of its programmable buttons, BLF (busy lamp field, standard or eventlist), call park/pick-up, speed dial, presence, intercom, and conference/transfer/forward. The GXP-2200EXT is the ideal solution for any receptionist or businesses managing high call volume. When using the GXP-2200EXT, the telephone attendant can ensure maximum productivity by efficiently monitoring and dispatching multiple incoming calls.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL	
Dimensions	206mm(L) x 117mm(W) x 32mm(H)
Weight	0.38kg
Temperature	0 - 40ºC
Humidity	10%-90% Non-condensing
Lines	20 per page (each module contains 2 pages, for up to 40 lines per module; Up to 160 with 4 daisy-chained modules
Feature Support	Local GUI with animation driven from the host GXP2140 or GXP3240 phone; Multiple line/call appearances
Compliance	FCC/CE/C-Tick

Used With



GXP-2170

An Enterprise IP Phone for High-Volume Users

Item Number: 2200012003

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.