

1000705300

Control Room Master

DISCONTINUED

Description

- ✓ Compact rack console with single touch keys, handset and 4x20 character display with backlight.
- ✓ Call-in annunciation with full display - 256 priority levels.
- ✓ Queuing of calls according to priority and time of arrival.
- ✓ Parallel servers and transfer of command support.
- ✓ Display information on station name/number or Call Request description.
- ✓ Auto acknowledgment to call-in point by flashing station lamp and/or voice message.
- ✓ Access to stations, group calls, audio monitoring, P.A. zones, radio channels and telephone lines.
- ✓ 60 different display texts and 256 priority levels for technical alarms.

☑ Electret microphone with automatic sensitivity adjustment

This advanced control room master features a large 4 x 20 character alphanumeric display with backlight, full dialing key-pad, 10 programmable single touch keys, answer-next-in-queue key, handset, sensitive electret microphone and a powerful 1W loudspeaker. The station offers full loudspeaking conversation with automatic switching of the speech direction.

The four-line display gives full information on the current conversation and calls waiting in queue. The information includes directory number, name/location and priority level. Convenient answer-next-in-queue button allows you to respond to calls according to priority and time of arrival. For easy connection, the unit is provided with a RJ45 socket for audio. Two pair twisted telephone cable is required between the station and the exchange. The station requires a local +12V DC / 300 mA power supply. NOTE: The handset is optional.

Please order part number #92495 Handset Kit.

Specifications

GENERAL

Operation Voltage:	+12 V DC
Maximum Current:	300 mA
Cable Requirements:	Connected to local power supply (1119): 1 pair twisted cable (power), Connected to exchange: 2 pair twisted cable 24 AWG, 4,600 ft.
Temperature Range:	0o C to +40o C -- +32o F to +104o F
Humidity Range:	10% - 85% RH
Dimensions:	5 1/4" W x 19" D x 2 1/2" H
Finish:	Black
Loudspeaker Output:	1 W (63 Ohm)
Loudspeaker Impedance:	63 Ohm
Loudspeaker Sound Pressure:	75 dB (0.5 mm cable x 100 m,5VRMS on ab-wire, 1 kHz)
Frequency Range:	300 - 5000 Hz
Connector Type:	1 x RJ45, includes MOS connector, 1-2 screw terminal for power
Indicator:	LED (red)

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1000705300	Control Room Master Station	