

1000705301

Control Room Master



DISCONTINUED

Description

- ✓ Compact desk console, single touch keys, hand-set and 4x20 character display with backlight
- ✓ Call-in annunciation with full display information and 256 priority levels
- ✓ Queuing of calls according to priority & arrival time
- ✓ Parallel servers and transfer of command support
- ✓ Display information on station name/number or Call Request description
- ✓ Auto acknowledgment to call-in point by flashing station lamp and/or voice message
- ✓ Access to stations, group calls, audio monitoring, P.A. zones, radio channels and telephone lines
- ✓ 60 different display texts and 256 priority levels for technical alarms

- ✓ Electret mic. with automatic sensitivity adjustment

This advanced control room master features a large 4 x 20 character alphanumeric display with backlight, full dialing keypad, 10 programmable single touch keys, answer next in queue key, handset, sensitive electret microphone and a powerful 1W loudspeaker. The station offers full loudspeaking conversation with automatic switching of the speech direction. Manual override of speech direction is also possible. The station's four-line display gives full information on the current conversation and calls waiting in queue. The information includes directory number, name/location and priority level. Convenient answer-next-in-queue button allows you to respond to calls according to priority and time of arrival. For easy connection, the unit is provided with a RJ45 socket for audio. 2-pair twisted telephone cable is required between the station and the exchange. The station requires a local +12V DC / 300 mA power supply (1119).

NOTE: The handset is optional. Please order part number #92497 Handset Kit.

Specifications

GENERAL

Operation Voltage:	+12V DC
Maximum Current:	300mA
Cable Requirements:	Connected to local power supply (1119): 1 pair twisted cable (power). Connected to exchange: 2 pair twisted cable 24 AWG, 4,600 ft.
Temperature Range:	0o C to +40o C -- +32o F to +104o F
Humidity Range:	10% - 85% RH
Dimensions:	14" W x 7" D x 3" H
Finish:	Black
Loudspeaker Output:	1 W (63 Ohm)
Loudspeaker Impedance:	63 Ohm
Loudspeaker Sound Pressure:	75 dB (0.5 mm cable x 100 m,5VRMS on ab-wire, 1 kHz)
Frequency Range:	300 - 5000 Hz
Connector Type:	1 x RJ45, includes MOS connector
Indicator:	LED (red)

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1000705301	Control Room Master Station	