

2310111065 S6230-ESGL1

Outdoor Spectra Enhanced HD1080p Stainless Steel



🂭 IP66

Description

The high-speed IP-PTZ dome cameras take a leap in image quality with the new Spectra® Enhanced product offering. The top tier dome provides industry-leading image quality with a wide dynamic range (WDR) imaging system, 60 images per second video (ips), electronic image stabilization, and a whole host of features such as image defog and Pelco's full suite of behavioral analytics.

✓ SureVision 3.0 Technology, Including:

- 3130 dB Wide Dynamic Range (WDR)
- ⊘ Advanced Low Light Down to 0.03 LUX on Select Models
- Anti-Bloom Technology
- 3D Noise Filtering
- Enhanced Tone Mapping
- ✓ Up to Full HD 1080p and up to 60 Images per Second (ips)

page 1/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

- ✓ Power over Ethernet (HPoE and PoE+), 24 VAC, 24 VDC
- H.264 Smart Compression Technology
- ⊘ Three Automatic Defog Options
- Electronic Image Stabilization (EIS)
- Built-in Analytics Suite
- Vandal Resistant IK10 Smoked or Clear Bubble
- SDXC Memory Card with up to 2TB
- ✓ Compatible with Pelco and Third-Party Video Systems

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Dimensions (ØxH)	218 x 282mm
Weight	3,1 Kg
Power	PoE
Power with heater	24VAC (3amp)
Camera Sensor Type	1/2.8 inch Type Exmor CMOS Sensor
Camera Optical Zoom	30X
Digital Zoom	12X
Maximum Resolution	1920 x 1080
Horizontal Angle of View	63.7° Wide - 2.3° tele
Day/Night Capabilities	Yes
Signal-to-Noise Ratio	> 50dB
Wide Dinamic Range	130 dB
Active Noise Filtering	3D Noise Filtering
Electronic Image Stabilization	Yes

Accessories



IDM4012SS

Bracket for Spectra dome stainless steel SD-429 & amp; S6230

page 3/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.