

2310111140

DS-6701HWI

One channel Video to IP encoder

DISCONTINUED

Description

- ✓ H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- ✓ Up to WD1 real-time encoding
- ✓ One PoE network interface
- ✓ Connectable with network HDD in NAS, IPSAN mode
- ✓ Support multiple network protocols, including IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3, OnVIF, PSIA, SOCKSv4/v5.
- ✓ Multiple PTZ protocols

Specifications

DESCRIPTION

Video Compression	H.264/MPEG4/MPEG2/ MJPEG
Video input	1-ch, BNC (1.0 Vp-p, 75 Ω)
Audio compression	G.711
Audio input	1-ch, 3.5mm interface (2.0 Vp-p, 1 k Ω)
Two-way audio	1-ch, 3.5 mm audio (2.0 Vp-p, 1 k Ω) (Line in)
Audio output	1-ch, 3.5mm interface (Linear, 600 Ω)
Encoding resolution	WD1/4CIF/2CIF/CIF/QC IF
Frame rate	H.264/MPEG4/MPEG2 encoding: 25 fps (P) / 30 fps (N); MJPEG encoding: 15 fps
Video bit rate	32 Kbps ~ 3072 Kbps, or user defined (Max. 8192 Mbps)
Audio bit rate	64 Kbps
Alarm in/Alarm out	1/1
Power supply	12 VDC, or PoE
Consumption	$\leq 6W$
Dimension(W×D×H)	80 × 39 × 90 mm
Weight	≤ 0.5 Kg
Working temperature	-10°C~+55°C
Working humidity	10%~90%

OTHER MODELS

2310111139	DS-6704HWI Four channel Video to IP encoder
------------	---