

2310120104

DS-6404HDI-T

High definition decoder 4-ch

DISCONTINUED

Description

- ✓ Supports private H.264, standard H.264, MJPEG, MPEG2 and MPEG4 video stream formats
- ✓ High-definition video output via DVI/VGA/HDMI interfaces and standard-definition video output via BNC interface
- ✓ Decodes video stream at resolution of 8MP, 5MP, 3MP, 1080p, 720p, SVGA, VGA, 4CIF, DCIF, 2CIF, CIF and QCIF
- ✓ Gets stream and decodes via channel zero, HiDDNS and VGA/DVI local channel (not supported by DS-6401HDI-T)
- ✓ VCA decoding
- ✓ Window spanning, floating, and windowing
- ✓ One 10/100/1000Mbps self-adaptive Ethernet interface
- ✓ Supports TCP, UDP and Multicast network protocols
- ✓ Multiple DDNS settings: Peanut Hull, Dyndns, IPServer, NO-IP and HiDDNS

Specifications

DESCRIPTION

Video input	1-ch, VGA connector; 1-ch, DVI-I connector; XGA@60Hz, 720P@60Hz, 720P@50Hz, UXGA@60Hz, SXGA@60Hz, 1080P@50Hz, 1080P@60Hz, 1080I@50Hz, 1080I@60Hz, WXGA@60Hz, WSXGA+@60Hz
Audio output	4-ch, DB15 connector
CVBS Output	2-ch without audio; DB15 connector (used with the DB15-to-BNC adapter)
DVI Output	4-ch; 1920 × 1080@60/50Hz, 1600 × 1200@60Hz, 1280 × 1024@60Hz, 1280 × 720@50/60Hz, 1024 × 768@60Hz
Video Stream Format	H.264/MJPEG/MPEG4/MPEG2/Private
Audio Stream Format	G.722/G.711A/G.711U/MPEG2-L2/AAC
Decoding Capability	8MP: 2-ch; 5MP: 4-ch; 1080p: 8-ch; 720p: 16-ch; 4CIF: 32-ch
Split Screen	1/4/9/16
Screen Spanning Mode	1 × 2, 1 × 3, 1 × 4, 2 × 1, 2 × 2
Decoding Capability	1/4 decoding capability contrast to the normal mode
	10/100/1000 Mbns self-

Network Interface	adaptive Ethernet interface
Serial Interface	1 RS-232 (DB9), 1 RS-485
Two-Way Audio In	1-ch, 3.5 mm connector (2.0 Vp-p, 1 kΩ)
Two-Way Audio Out	1-ch, 3.5 mm connector (2.0 Vp-p, 1 kΩ)
Alarm In/Alarm Out	4/4
Power supply	100 to 240 VAC
Consumption	≤ 108 W
Dimension(W×D×H)	440 × 340 × 70 mm
Weight	5.2 Kg

OTHER MODELS

9011811006	DS-6408HDI-T high definition decoder 8ch
------------	--