



2310111125

LAS60-57CN-RJ45

60W High PoE midspan (PoE injector) 110-230VAC

- Ompatible With All IEEE pre 802.3af, 802.3at and Legacy Powered Devices
- Input voltage:90Vac~264Vac
- Support 300Vac input for long time work
- Output over current protection
- Short circuit protection
- MTBF ≥1,000,000 hrs
- Surge protection
- CE mark
- ✓ WEEE compliant
- RoHS compliant

Description

The LAS60-57CN-RJ45 midspan is designed to extract power from a conventional twisted pair Category 5 Ethernet cable, conforming to the IEEE 802.3at Power-over-Ethernet (PoE) standard. The converter signature and control circuit provides the PoE compatibility signature and power classification required by the Power Sourcing Equipment (PSE) before applying up to 60W power to the port.

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

DESCRIPTION

Input Current	2A
Output Voltage Range	54V~57V
Output Power	60W
Ports	2x 10/100/1000M adaptive RJ45 ports, one is DATA/IN, another is PoE/DATA
LED Indicator	Power & PoE Status(The module operates normally when MID and END are on)
Base Function	Compliance to IEEE 802.3 at/af Standard for PD
Protection Methods	Output Over Current Protection, Short Circuit Protection
Operating Humidity	5% ~ 90%
Weight	473g
Dimension (LxWxH)	185mmx70.8mmx37mm
Operating Temperature	-20 ~ 60

Used With





4MP 25× Network IR Speed Dome PTZ camera



Explosion-Proof IP Bullet Camera, 2MP, w/ wiper



iDS-2CD7A26G0-IZHSY WDR IR Varifocal Bullet Network Camera

Bullet Network Camera

page 2/2

camera