

2310111094

NX-PTZ-HD11VW0Z00B

Outdoor IP Camera, SST, 1080p, IP68





Description

- ✓ LR Type approved PTZ IP camera, 316L stainless steel
- Camera Full HD 1080p, 30x, 60fps
- Integrated screen wiper
- 230VAC, 120W (optional models 24VAC, 120VAC)
- ✓ Video compression H.264/AVC, MJPEG, JPEG and MPEG4
- O Up to 3 simultaneous video streams in FULL HD
- Operating temperature:from-40°C to+60°C
- Protection degree:IP66,IP67,IP68,IP69
- ⊘ 3m pigtail included. JB needed for cable termination.

page 1/4

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

NXPTZHD11VW0Z00B is a Full HD PTZ camera which integrates new imaging and encoding technology for outdoor video surveillance, allowing recordings to be produced with incredibly bright and vivid colours both by day and by night.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

DESCRIPTION

Supply voltage/Current consumption	30Vac, 0.5A max, 50/60Hz
Power consumption	120W max
Ethernet connection	RJ45 100 Base-TX
Device configuration	TCP/IPv4-IPv6, UDP/IPv4-IPv6, HTTP, HTTPS, NTP, DHCP, WS-DISCOVERY, DSCP, IGMP (Multicast), SOAP, DNS
Video compression	H.264/AVC, MJPEG, JPEG, MPEG4
Video streams	3 independent video streams Full HD
Image resolution	From 320x180pixel to 1920x1080pixel in 6 steps
Selectable frame rate	From 1 to 60 images per second (fps)
I/O alarm board	Alarm inputs: 1; Relay outputs: 1 (1A, 30Vac/60Vdc max)
Resolution	Full HD 1080p (1920x1080pixel)
Image Device	1/2.8" Exmor™ R CMOS sensor
Effective Pixels	Approx. 2.38 Megapixels
Minimum Illumination	Colour: 0.006lx (F1.6, 30 IRE); B/W: 0.0006lx (F1.6, 30 IRE)
Focal length	From 4.5mm (wide) to 135mm (tele)
Zoom	30x (480x with digital zoom)

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Iris	From F1.6 to F9.6,10 steps (Auto, Manual)
Horizontal Viewing Angle	From 61.6° (wide end) to 2.50° (tele end)
Vertical Viewing Angle	From 37.07° (wide end) to 1.44° (tele end)
Shutter speed	From 1/1s to 1/10000s (Auto, Manual)
Gain	From 0dB to 36dB (Auto, Manual)
Wide Dynamic Range	120dB
Operating temperature	From -40°C to +60°C
Relative humidity	From 10% to 95% (no condensation)
Weight	22kg

Accessories





NX-TA-WA

Outdoor IP Camera Washer, 23I, 230/24VAC FM1010 EMC Filter

EMC filter for Marine certification



WASEX2T4AT EX

WASEX WASHER PUMP WITH EX-PROOF SOLENOID VALVE

page 4/4

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.