

3006220002

**26103**

U914T, Pocket Receiver with Display and Vibrator, 457.575MHz



- ✓ IP64: Durable design, Robust and shock resistant
- ✓ Message Alarm priority identified by the signal
- ✓ Group paging available
- ✓ Seven individually programmable beep signals and silent mode for meetings
- ✓ Reminder function that indicates at regular intervals that there are unread messages
- ✓ Easy to reprogram via storage/charging rack or radio
- ✓ Automatic out-of-range warning and battery test
- ✓ HF Frequency Band: H914T and UHF Frequency Band: U914T models

---

## Description

A robust pager designed for heavy usage in demanding environments. It is splash resistant and dust proof, in accordance with IP64 classification, plus impact resistant. Message priority indication, with distinct beep codes, helps to ensure that critical alerts are not missed.

Also available in an "intrinsically safe" model, designed for use in potentially explosive environments.

# Specifications

## GENERAL

Dimensions (LxWxD)	86x51x19 mm
Weight	84g including battery
Operating temperature	-10°C to +50°C
Message length	120 characters
Storage capacity	10 messages
Sound pressure level	> 93 dBA at 10 cm
Frequency range	425-470 MHz

## PRODUCT VARIANTS

3006220002	U914T, Pocket Receiver with Display and Vibrator. 457.575 Mhz
2310213002	U914T Pocket Receiver with Display and Vibrator 457.525 Mhz
2630400004	EX U914T Pocket Receiver with Vibrator, without Display. 469.250Mhz
2630400001	EX U914T Pocket Receiver with Vibrator, without Display 412-427 MHz
3006120012	EX U914T, Pocket Receiver with Display and Vibrator. 457.575MHz
3006220004	H914T Pocket Receiver with Vibrator, 27.3 Mhz

## ACCESSORIES

3006120014	PENLIGHT BATTERY TYPE IEC LR03 (AAA) (1 PER RECEIVER)
------------	---