

4000016818

P-1601 PAGA Control Unit

Note: This product is only available as spare part.



Description

- ✓ Gooseneck Microphone
- ✓ RS485 data communication with MPA P-1600 Operation Unit
- ✓ 6-zone selection keys
- ✓ PA (normal paging) key
- ✓ Emergency PA key marked with red color
- ✓ Emergency PA key is protected against unauthorized use by means of time-trap functionality (the emergency PA key must be held for 1 sec before activation)
- ✓ Dimmer key
- ✓ Status LED for system A and system B
- ✓ LED indicators for all keys
- ✓ Dimmable backlight and indication LEDs
- ✓ Local mute relays
- ✓ Complies with IEC 60945 Standard for Marine Equipment

The MPA P-1601 is a full facility operator control unit in the MPA system. It is designed for flush mounting.

Specifications

MECHANICAL

Dimensions (WxHxD)	144x144x43 mm (depth behind console excluding cables)
Weight	0.6 kg
Color	RAL 9005 / Natural
Material	Aluminium / Steel
Mounting	Console
Fixing	4 x M4 bolts
Access	Front
Cable Entry	Rear
Cable Type	3-pair cable, twisted pairs, min. 3x2x0.5 mm ²

ELECTRICAL

Power Supply	24VDC from Control rack (+/- floating)
Frequency Range	300-5000 Hz
Power Consumption	7.2 W
Microphone Input Level	10 mV
Termination	Termination Block
Compass Safe Distance	80 cm

ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	20% to 80% non-condensing
Ingress Protection Rating	IP-44