4000018361 / 4000100030

ICS 6200

Central Unit

- ✓ Up to 24 analog or digital lines per unit
- ✓ 48 VoIP registrations per unit
- ✓ 2 x 100 Mbit Ethernet ports
- ✓ Modular terminal interface design
- ✓ PBX features such as group calls, paging groups, alert groups, conferences, switchboard, direct inward dialling
- ✓ VoIP or FXO trunk lines
- ✓ SIP/RTP protocol support
- ✓ Dual redundant power supply
- ✓ Complies with IEC 60945 Standard for Marine Equipment
- ✓ DNV-GL, ABS, RMRS type approval and compatible with NORSOK

Description

The Phontech P-6200 Central Unit is a digital communication system meeting all aspects of internal and external communication, and information exchange on-board vessels, offshore installations and to/from onshore operation centers.

Up to six line boards can be added with the following interface formats:

- ✓ 4000017689 6200 FXS line board, 4 analogue lines
- ✓ 4000017839 6200 UpN line board, 4 digital lines
- ✓ 4000017836 6200 FXO line board, 4 analogue trunk lines
- ✓ 4000017838 6200 E&&M line board - 2 lines (4wire)

For systems that are not using purely IP extensions we recommend to also use the ICS 6205 RJ45 to D-sub patch panel (item no. 4000018364), cable organizer (item no. 4000018586) as well as our eight-line termination module kit (item no. 4000018526).

Technical Dimensions

www.zenitel.com   info@zenitel.com

Rear View

31.70

10,5×7

445.00
465.00

Side View

246.00

Front View

44.00

POWER ○
INFO ○
ERROR ○

∧
○ ○
< ○ >
○
∨

PHONTECH 6200

x ○
√ ○

1 3 5 7 9 11   13 15 17 19 21 23
2 4 6 8 10 12   14 16 18 20 22 24

LAN1 LAN2

483.00

Specifications

MECHANICAL

Dimensions	19" 1U rack mounted, D=246 mm
Weight	3.5 kg
Color	RAL 9005
Material	Steel / Plastic
Mounting	Rack/ Console
Fixing	2 x M5 bolts
Access	Front
Cable Entry	Rear and Front
Connector Type	RJ45

ELECTRICAL

Power Supply	220/110 VAC, 48/24 VDC (dual redundant)
Power Consumption	12 W (idle), 65 W (max)
Heat Dissipation	35 W (max)
Compass Safe Distance	0.2 m

ENVIRONMENTAL

Temperature	0°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-20

PRODUCT VARIANTS

4000018361	ICS 6200 Basic Unit AC/DC Power
4000100030	ICS 6200 Basic Unit AC/AC Power
1150103009	ICS 6200 Basic Unit AC/DC Power w/installation, incl. patch panel, cable organizer and patch cable
1150103010	ICS 6200 Basic Unit AC/AC Power w/installation, incl. patch panel, cable organizer and patch cable

www.zenitel.com   info@zenitel.com