

3006100026

CAU-4T

Wall Loudspeaker Watertight, 4W - IP-55



Description

THIS PRODUCT IS NO LONGER AVAILABLE

- ✓ Waterproof wall loudspeaker w/transformer for use in galleries, etc.
- ✓ With 100V line transformer
- ✓ Adjustable power tapping
- ✓ Aluminium

When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was received. Fasten loudspeaker to wall by 1-3 screws on the bracket. To change the position of the loudspeaker, adjust the bracket (by loosening / tightening the screws) as required. For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated. Do not open loudspeaker when energized. Fasten lid with a torque of 2 - 3 Nm.

Specifications

GENERAL

Material/Color	Aluminium / RAL 7035
Mounting	Bracket
Termination	Spring clamp
Dimension (WxHxD)	128 x 237 x 100 mm
Weight	1,9 kg
IP- rating	IP-55
Max. / min. amb. temp	90°C / -40°C
Rated / max. power	4 W / 6 W
SPL 1W/1m	90 dB
SPL rated power	96 dB
Effective freq. range	160 – 16000 Hz
Dispersion (-6dB) 1kHz / 4kHz	160° / 110°