

3006100026

CAU-4T

Wall Loudspeaker Watertight, 4W - IP-55



Description

THIS PRODUCT IS NO LONGER AVAILABLE

- ✓ Waterproof wall loudspeaker w/transformer for use in galleries, etc.
- ✓ With 100V line transformer
- ✓ Adjustable power tapping
- ✓ Aluminium

When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was received. Fasten loudspeaker to wall by 1-3 screws on the bracket. To change the position of the loudspeaker, adjust the bracket (by loosening / tightening the screws) as required. For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated. Do not open loudspeaker when energized. Fasten lid with a torque of 2 - 3 Nm.

Specifications

GENERAL

| | |
|----------------------------------|----------------------|
| Material/Color | Aluminium / RAL 7035 |
| Mounting | Bracket |
| Termination | Spring clamp |
| Dimension (WxHxD) | 128 x 237 x 100 mm |
| Weight | 1,9 kg |
| IP- rating | IP-55 |
| Max. / min. amb. temp | 90°C / -40°C |
| Rated / max. power | 4 W / 6 W |
| SPL 1W/1m | 90 dB |
| SPL rated power | 96 dB |
| Effective freq. range | 160 – 16000 Hz |
| Dispersion (-6dB) 1kHz / 4kHz | 160° / 110° |