

2310111006

FlexiDome VDC-455V03 Camera

Color camera for indoor/outdoor

Product image
not available

Description

- ✓ Low-impact and impact-resistant models
- ✓ 1/3-inch format CCD imager
- ✓ Superior picture clarity in virtually all situations
- ✓ 540 TVL color resolution
- ✓ AC or DC operation
- ✓ Patented dome shape for 90° vertical view
- ✓ Extended sensitivity with NightSense
- ✓ Bilinx bi-directional communication

The FlexiDomeVF and FlexiDomeXT+ series of dome cameras are an excellent solution for virtually any indoor or outdoor application. The cast aluminum housing, polycarbonate dome and hardened inner liner of the FlexiDomeXT+ version can withstand the equivalent of 120 lbs of force. The FlexiDomeVF utilizes a standard indoor enclosure. These units contain full-featured color and monochrome cameras, with 1/3-inch CCD and integral varifocal lenses.

Installation is quick and easy, since the cameras come completely assembled and ready to use. Using the proprietary pan/tilt/rotation mechanism, installers can select exactly the required field of view. Mounting options are numerous, including surface, 4S, wall, corner and suspended ceiling.

The FlexiDomeVF and FlexiDomeXT+ cameras are an ideal solution for many surveillance applications. Their compact, sleek design

and virtually flush-mount appearance complement any decor. The camera enclosure provides the extra protection necessary for applications such as in schools, banks, prisons, parking garages, retail and commercial buildings.

Specifications

CERTIFICATIONS AND APPROVALS

Safety	UL1950; CSA 22.2 No.950; EN 60950 (CE)
Immunity	EN 50130-4 (CE)
Emission	EN 50022 class B (CE); FCC, class B part 15
Water/dust protection	IP66 and NEMA-4X (VDM- 355 and VDC-455models only)