

2220012144

2960X-24TD-L

CISCO Catalyst 2960X 24-port 10/100/1000 Switch with 2x10GE Uplinks



Description

Cisco Catalyst 2960-X Series Switches are fixed-configuration, stackable Gigabit Ethernet switches that provide enterprise-class access for campus and branch applications. Designed for operational simplicity to lower total cost of ownership, they enable scalable, secure and energy-efficient business operations with intelligent services and a range of advanced Cisco IOS Software features.

Specifications

The Cisco 2960X-24TD-L is managed 24-port switch with 24 auto-sensing 10/100/1000 ports and 2x 10 Gigabit Ethernet SFP+ ports.

ENVIRONMENT

| | |
|-----------------------------|---------------------------|
| Operating temperature | 23° to 113°F (-5°to 45°C) |
| Operating relative humidity | 10% to 95% noncondensing |

ELECTRICAL CHARACTERISTICS

| | |
|--------------------------|---------------|
| Frequency | 50/60 Hz |
| Maximum heat dissipation | 112.94 BTU/hr |
| AC voltage | 100 / 240 VAC |
| Current | 1 / 0.5 A |
| Maximum power rating | 33.1 W |

DIMENSIONS & WEIGHT

| | |
|------------------------|---------------------|
| Dimensions (W x D x H) | 445 x 279 x 45 mm |
| Weight | 4 kg |
| Mounting | Rack Mountable, 1HU |