

2220012135

2960X-48FPD-L

CISCO Catalyst 2960X 48-port 10/100/1000 PoE+ Switch with 2x10GE Uplink



Description

Cisco Catalyst 2960-X Series Switches are fixed-configuration, stackable Gigabit Ethernet switches that provide enterprise-class access for campus and branch applications. Designed for operational simplicity to lower total cost of ownership, they enable scalable, secure and energy-efficient business operations with intelligent services and a range of advanced Cisco IOS Software features.

Specifications

The Cisco 2960X-48FPS-L is managed 48-port switch with 48 auto-sensing 10/100/1000 PoE+ ports and 2x10 Gigabit Ethernet SFP+ ports.

ENVIRONMENT

Operating temperature	23° to 113°F (-5°to 45°C)
Operating relative humidity	10% to 95% noncondensing

ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
Maximum heat dissipation	2752.91 BTU/hr
AC voltage	100 / 240 VAC
Current	9 / 4 A
Maximum power rating	806.8 W
Available PoE power	740 W (24 ports up to 30W or 48 ports up to 15.4W)

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 368 x 45 mm
Weight	5.8 kg
Mounting	Rack Mountable, 1HU