



#### 1008123120

# TFIX-2-V2

#### Ex IP Intercom Station with 6 buttons

- Ex IP intercom for potentially explosive atmospheres Directive 2014/34/EU
- Ethernet compatible 2-wire interface
- ONVIF Compatible
- DIP functionality for use with AlphaCom audio servers
- SIP/VoIP functionality for use with 3rd-party systems
- Dust- and water-protected to IP66
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- Integrated 25W amplifier for external loudspeaker
- Signal relay for external beacon

















Active Noise Cancelling



IP over 2-wire

# Description

The TFIX-2-V2 Explosion-proof intercom station is a rugged device, designed for harsh environments and meets industrial and offshore requirements as well as requirements for ATEX Zone 1 operation. The plastic housing is designed to withstand most chemical and environmental hazards found on- or offshore.

The TFIX-2-V2 features 6 programmable buttons.


The intercom station is fully digital and offers crystal clear audio with high output through an internal amplifier and 78 mm speaker, delivering over 90 dB SPL. Active Noise Reduction and Acoustic Echo Cancelling allows for hands-free two-way communication with superior audio quality. A built in 25W amplifier is also included to power an external Loudspeaker.

Intercom status indicators display the status of the system and are compatible with AlphaCom and Exigo systems as well as SIP functionality for use with 3rd party systems.

# **Technical Dimensions**

page 1/5

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.



# **Specifications**

## **MECHANICAL**

Dimensions	345 x 178 x 101 mm
Weight	4 kg
Mounting	On-wall box (included)
Color	Black

#### **ENVIRONMENTAL**

Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +70°C
Operating humidity	10% to 95% RH (non-condensing)
Storage humidity	10% to 95% RH (non-condensing)
Air pressure	600 hPa to 1200 hPa
IP-rating	IP64 in accordance with IEC 60079-0
	IP66 in accordance with EN 60945
IK rating	4J

#### **ELECTRICAL**

PoE	NO, proprietary 2-wire data- and powerbus	
Power consumption	4.2 W (idle) to 8 W (max), 38.5W (max) with external loudspeaker	
DC power	24-48 VDC (SELV)	
	48 DVC PSU required when using external amplifier (One FCDC3 per station is also recommended when using external amplifier)	

page 3/5

#### **NETWORK**

Connection	2 x 2-wire
Connection type	Screw terminals
Functions	Auto negotiating
Built-in switch	N/A
Compatibility	SIP, ICX-AlphaCom, IC- EDGE, G.711, G.722, G.729, HD Voice, ONVIF

## **INPUTS AND OUTPUTS**

Handheld Microphone	Microphone (bal), PTT
Handset	Microphone (bal), Speaker (bal) + PTT
Headset	Microphone (bal), Speaker (bal), + PTT
Digital inputs/outputs	2 (Ex i type)
Relay outputs	1 (60VDC, 320mA, 10^8 operations)
Audio	Yes, for audio accessories
Aux power	Provided by network cable
External speaker amplifier	25W class D
External speaker specifications	Impedance=80hm, minimum rated power: 25W
	Impedance=20Ohm, minimum rated power: 10W

## **CERTIFICATIONS**

Immunity	EN 60945, EN 61000-6-2
Emission	EN 60945, EN 61000-6-3, EN 61000-6-4
CENELEC safety standards	EN 60079-0:2018, EN 60079- 7:2015/A1:2018, EN 60079- 11:2012, EN 60079- 18:2015/A1:2017
IEC safety standards	IEC 60079-0:2017, IEC 60079-7:2017, IEC 60079- 11:2011, IEC 60079-18:2017
Marking	II 2(2) G Ex e ib mb [ib] IIC T4 Gb -20°C ≤ Ta ≤ +55°C

page 4/5

#### OTHER SPECIFICATIONS

Warranty

2 Years standard warranty, extendible up to total of 5 years (additional fee)

# Accessories



AK5850HS

Ex-approved Headset



TAX-2B

Ex-Approved Plugbox & Dry Cable for Headset with PTT



TAX-3

EX Handset



#### EMMAX-1H

Handheld Industrial EX
Microphone For Exigo/Turbine



#### FCDC3

Flowire Ethernet Converter - DC Voltage



Power Supply 100-240VAC/48VDC 2A



DSP-15 EExmN, 25W

Ex horn speaker for TFIX-V2 stations, 8 Ohm



## TNFCD2G212

Ex proof beacon, Ex de 24-48VDC GREEN, 1 x M25 gland