



2340032010

DK 10/T-EN54-PG

EN54 horn speaker 10 watt

- NEW built-in junction box
- High sound pressure level
- Weather proof

IP66

Description

Weatherproof horn speaker for voice alarm applications, certified according to EN 54-24, suitable for industrial indoor and outdoor use with high sound pressure level.

The 10W powered speaker is equipped with a 100V line transformer with 4 power adjustments, also low-impedance operation (20 ohm) is possible. The impact-resistant ABS housing UL94V0 in RAL 7035 guarantees long-term stability. For additional reliability, a ceramic block and a thermal fuse is provided in a junction box.

The speaker is also secured with the high protection class IP 66 against the security risks of environmental influences.

Included is a U-shaped, stainless steel universal mount for flexible installation. Optionally available is a mast bracket (MB) for about 90 - 200mm mast diameter.

page 1/2

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

| CHARACTERISTICS | VALUE |
|-------------------------------|----------------------|
| Power | 10/5/2,5/1,25 (20) W |
| Frequency Range | 569 - 7.000 Hz |
| Frequency Response | 370 - 13.600 Hz |
| SPL 1W/1m, peak | 106,7 dB |
| SPL, 1W/4m, peak | 94,7 dB |
| SPL Pmax/4m, peak | 104,7 dB |
| Sensitivity EN54-24, 1W/4m | 83 dB |
| Dispersion -6dB, 500Hz | 360° |
| Dispersion -6dB, 1KHz | 360° |
| Dispersion -6dB, 2KHz | 105° |
| Dispersion -6dB, 4KHz | 50° |
| Connector | ceramic block |
| Maximum cable cross section | 8mm² |
| Max. cable cross section loop | 2x2mm² |
| Temperature range | -25 / +70 °C |
| Dimensions | 142x256 mm |
| IP Rating | IP66 |
| Weight (net) | 1,90 kg |
| Colour | RAL 7035 |
| Mounting | Mounting bracket |
| Certificate Number | 1438/CPR/0242 |